



BETTER SOLUTIONS ARE THE RESULT OF CONVINCING DETAILS.

Winger

Optimized agitator for water-based paint



Not homogenized or not enough homogenized paint and varnish lead to quality problems in the coating process. Prior to processing the supply containers must be thoroughly agitated. REITER GmbH + Co. KG Oberflächentechnik developed therefore in working relationship with users and the paint industry an optimized solution for this functional specification.

The Winger has many advantages compared to the solutions that are available at the market at the moment. Its geometry allows the certain reach to the container rims in all generally used supply containers up to 200l.

Liquids up to 100 DIN 4s are being homogenized gently with the lowest shearing force and without danger of trapped air.

The cleaning friendly design in connection with a quick changing device makes the agitating process easier.

Through easy adaptation to existing drives retrofitting is possible without any problems.

Area of application

- Water-based paint
- Solvent-based paint
- High solid paint
- 30l container
- 120l container
- 200l container

Features

- Quick changing device
- Cleaning friendly
- Optimal reach to the rim
- Low shearing force

Technical Data

Winger – Optimized agitator for water-based paint

Dimensions:	Length variable up to 900 mm
Agitating disc:	ø 200 mm
Driving power:	0,5 kW
Disc rotation:	15 - 90 U/min.
Agitator shaft tie-down:	ø 16 mm

